



Afmetingen

Artikelnummer	D	R	H	d1	M	d	L
GM-2BP-R0.3-M06 KMG303	0,60	0,3	0,9	0,55	6	4	50
GM-2BP-R0.4-M04 KMG303	0,80	0,4	1,2	0,75	4	4	50
GM-2BP-R0.4-M06 KMG303	0,80	0,4	1,2	0,75	8	4	50
GM-2BP-R0.4-M08 KMG303	0,80	0,4	1,2	0,75	8	4	50
GM-2BP-R0.4-M10 KMG303	0,80	0,4	1,2	0,75	10	4	50
GM-2BP-R0.5-M04 KMG303	1,00	0,5	1,5	0,95	4	4	50
GM-2BP-R0.5-M06 KMG303	1,00	0,5	1,5	0,95	6	4	50
GM-2BP-R0.5-M08 KMG303	1,00	0,5	1,5	0,95	8	4	50
GM-2BP-R0.5-M10 KMG303	1,00	0,5	1,5	0,95	10	4	50
GM-2BP-R0.5-M12 KMG303	1,00	0,5	1,5	0,95	12	4	50
GM-2BP-R0.6-M06 KMG303	1,20	0,6	1,8	1,15	6	4	50
GM-2BP-R0.6-M08 KMG303	1,20	0,6	1,8	1,15	8	4	50
GM-2BP-R0.6-M12 KMG303	1,20	0,6	1,8	1,15	12	4	50
GM-2BP-R0.6-M16 KMG303	1,20	0,6	1,8	1,15	16	4	50
GM-2BP-R0.75-M08 KMG303	1,50	0,75	2,3	1,45	8	4	50
GM-2BP-R0.75-M12 KMG303	1,50	0,75	2,3	1,45	12	4	50
GM-2BP-R0.75-M16 KMG303	1,50	0,75	2,3	1,45	16	4	50
GM-2BP-R1.0-M06 KMG303	2,00	1	3	1,95	6	4	50
GM-2BP-R1.0-M08 KMG303	2,00	1	3	1,95	8	4	50
GM-2BP-R1.0-M10 KMG303	2,00	1	3	1,95	10	4	50
GM-2BP-R1.0-M12 KMG303	2,00	1	3	1,95	12	4	50
GM-2BP-R1.0-M16 KMG303	2,00	1	3	1,95	16.0	4	50
GM-2BP-R1.0-M20 KMG303	2,00	1	3	1,95	20	4	50
GM-2BP-R1.25-M08 KMG303	2,50	1,25	3,7	2,4	8	4	50
GM-2BP-R1.25-M12 KMG303	2,50	1,25	3,7	2,4	12	4	50
GM-2BP-R1.25-M16 KMG303	2,50	1,25	3,7	2,4	16	4	60
GM-2BP-R1.25-M20 KMG303	2,50	1,25	3,7	2,4	20	4	60
GM-2BP-R1.5-M08 KMG303	3,00	1,5	4,5	2,85	8	6	50
GM-2BP-R1.5-M10 KMG303	3,00	1,5	4,5	2,85	10	6	50
GM-2BP-R1.5-M12 KMG303	3,00	1,5	4,5	2,85	12	6	50
GM-2BP-R1.5-M16 KMG303	3,00	1,5	4,5	2,85	16	6	60
GM-2BP-R1.5-M20 KMG303	3,00	1,5	4,5	2,85	20	6	60
GM-2BP-R2.0-M10 KMG303	4,00	2	6	3,85	10	6	60
GM-2BP-R2.0-M16 KMG303	4,00	2	6	3,85	16	6	60
GM-2BP-R2.0-M20 KMG303	4,00	2	6	3,85	20	6	60
GM-2BP-R2.0-M25 KMG303	4,00	2	6	3,85	25	6	60
GM-2BP-R2.5-M16 KMG303	5,00	2,5	7,5	4,85	16	6	60
GM-2BP-R2.5-M25 KMG303	5,00	2,5	7,5	4,85	25	6	70

Materiaal		Vc m/min	0,3 t/m 0,7mm	0,8 t/m 1,0mm	2 t/m 3mm	Fz (voeding) mm/omwenteling 4 t/m 5mm
Staal	Ongelegeerd staal ST37 ST52/3	130m/min (100-140)	0,01	0,02	0,02	0,03
	Laaggelegeerd staal C45 C60	95m/min (80- 100)	0,01	0,02	0,02	0,03
	Hoog gelegeerd staal 36CrNiMo4 42CrMo4	75m/min (60- 80)	0,01	0,02	0,02	0,02
Roestvrij	RVS ferritisch / martenitisch 403-416 - 420	45m/min (40- 50)	0,01	0,02	0,02	0,02
	RVS Austenitisch 303-304-316	40m/min (35- 45)	0,01	0,02	0,02	0,02