



## Face mill

FMR11



Article	*	Stock	Dimensions [mm]					Teeth	Coupling	kg	Insert
			R	ØD	ød	L	a <sub>p max</sub>				
FMR11-040-A16-RD10-06C	*	○	5	40	16	40	5	6	A	–	RD**10T3
FMR11-050-A22-RD10-07C	*	●	5	50	22	40	5	7	A	0,30	
FMR11-052-A22-RD10-07C	*	●	5	52	22	40	5	7	A	0,28	
FMR11-063-A22-RD10-08C	*	●	5	63	22	40	5	8	A	0,50	
FMR11-066-A22-RD10-08C	*	●	5	66	22	40	5	8	A	0,46	
FMR11-080-A27-RD10-09C	*	●	5	80	27	50	5	9	A	0,82	
FMR11-040-A16-RD12-05C	*	●	6	40	16	40	6	5	A	0,18	RD**1204
FMR11-050-A22-RD12-05C	*	●	6	50	22	40	6	5	A	0,27	
FMR11-050-A22-RD12-06C	*	●	6	50	22	40	6	6	A	0,27	
FMR11-052-A22-RD12-06C	*	●	6	52	22	40	6	6	A	0,27	
FMR11-063-A27-RD12-07C	*	●	6	63	27	40	6	7	A	0,39	
FMR11-066-A27-RD12-07C	*	●	6	66	27	40	6	7	A	0,40	
FMR11-080-A27-RD12-08C	*	●	6	80	27	50	6	8	A	1,00	
FMR11-040-A16-RP10-06C	*	●	5	40	16	40	5	6	A	0,19	RP**10T3
FMR11-050-A22-RP10-07C	*	●	5	50	22	40	5	7	A	0,29	
FMR11-052-A22-RP10-07C	*	●	5	52	22	40	5	7	A	0,29	
FMR11-063-A22-RP10-08C	*	●	5	63	22	40	5	8	A	0,48	
FMR11-066-A22-RP10-08C	*	●	5	66	22	40	5	8	A	0,49	
FMR11-080-A27-RP10-09C	*	●	5	80	27	50	5	9	A	0,93	
FMR11-040-A16-RP12-05C	*	●	6	40	16	40	6	5	A	0,16	RP**1204
FMR11-050-A22-RP12-06C	*	●	6	50	22	40	6	6	A	0,27	
FMR11-052-A22-RP12-06C	*	●	6	52	22	40	6	6	A	0,28	
FMR11-063-A27-RP12-07C	*	●	6	63	27	40	6	7	A	0,40	
FMR11-066-A27-RP12-07C	*	●	6	66	27	40	6	7	A	0,43	
FMR11-080-A27-RP12-08C	*	●	6	80	27	50	6	8	A	1,00	

● Ex stock ○ On demand

\* With internal cooling

### Spare parts

	Insert	RD**10T3	RD**1204	RP**10T3	RP**1204
	ØD	20 – 66	20 – 66	80	80
	Screw (insert)	I60M3,5*8 (2,7Nm)	I60M3,5*8 (2,7Nm)	I60M4*8,4 (3,4Nm)	I60M4*8,4 (3,4Nm)
	Wrench (insert)	WT15IP	WT15IP	WT15IS	WT15IS