



WN** steel boring bar P-Clamping

PWLNR/L Kr: 95°



Right hand style

Article	*	Stock		Dimensions [mm]							Inserts
		R	L	ød	L	h	s	e	D _{min}	θ	
S16M-PWLNR/L06	●	●	16	150	15	11	25	20	-13		WN**0604**
S16M-PWLNR/L06	●	●	16	150	15	11	25	20	-13		WN**0604**
S16R-PWLNR/L06	○	○	16	200	15	11	25	20	-13		WN**0604**
S20Q-PWLNR/L06	●	●	20	180	18	13	35	25	-13		WN**0604**
S20S-PWLNR/L06	●	○	20	250	18	13	35	25	-13		WN**0604**
S25Q-PWLNR/L06	○	○	25	180	23	17	35	32	-13		WN**0604**
S25T-PWLNR/L06	○	○	25	300	23	17	35	32	-13		WN**0604**
S20Q-PWLNR/L08	●	●	20	180	18	13	32	25	-13		WN**0804**
S20S-PWLNR/L08	●	○	20	250	18	13	32	25	-13		WN**0804**
S25Q-PWLNR/L08	●	○	25	180	23	17	45	32	-13		WN**0804**
S25T-PWLNR/L08	●	●	25	300	23	17	45	32	-13		WN**0804**
S32R-PWLNR/L08	●	●	32	200	30	22	50	40	-15		WN**0804**
S32U-PWLNR/L08	●	●	32	350	30	22	50	40	-15		WN**0804**
S50W-PWLNR/L08	○	○	50	450	47	35	50	63	-15		WN**0804**

● Ex stock ○ On demand

* With internal cooling

Spare parts					
	Insert	WN**0604**	WN**0804**	WN**0804**	WN**0804**
	ød	16-25	20-25	32	50
	Knee lever	L3B	L4A	L4	L4
	Screw	LEM5×12B (4.0 Nm)			
	Screw			LEM8×21 (10.2 Nm)	LEM8×21 (10.2 Nm)
	Screw		LEM6×13.4A (7.0 Nm)		
	Shim pin (shim)			SP4	SP4
	Shim			W08AP	W08AP
	Wrench		WH25L	WH30L	WH30L
	Wrench	WT09IP			

System code > A322

Grade selection > A42

Technical info > A501

Cutting data > A366