




Afmetingen



Artikelnummer	d1	Spoed	l1	l2	d2	a	DIN	 Ø mm
1720NX M3	M3	0,5	56	11	3,5	2,7	371	2,5
1720NX M4	M4	0,7	63	13	4,5	3,4	371	3,3
1720NX M5	M5	0,8	70	16	6	4,9	371	4,2
1720NX M6	M6	1	80	19	6	4,9	371	5,0
1720NX M8	M8	1,25	90	22	8	6,2	371	6,8
1720NX M10	M10	1,5	100	24	10	8	371	8,5
3720NX M12	M12	1,75	110	17,5	9	7	376	10,2

Materiaal		Vc m/min	F = toerental x spoed
Staal	Ongelegeerd staal	22-24m/min	
	ST37 ST52/3		
	Laaggelegeerd staal	18-22m/min	
	C45 C60		
	Hoog gelegeerd staal	7-12m/min	
36CrNiMo4 42CrMo4			
Roestvrijstaal	RVS ferritisch / martenitisch	10m/min	
	403-416 - 420		
	RVS Austenitisch	12m/min	
	303-304-316		
Gietijzer	Grijs gietijzer GG10-GG15-GG20	30m/min	
	GG25-GG30-GG35-GG40		
	Nodulair gietijzer	22m/min	
	GGG40-GGG50-GGG60-GGG70		
Non-Ferro	Aluminium	30-35m/min	