




Afmetingen



Artikelnummer	d1	Spoed	l1	l2	d2	a	DIN	 Ø mm
2220NX M3	M3	0,5	56	5	3,5	2,7	371	2,5
2220NX M4	M4	0,7	63	7	4,5	3,4	371	3,3
2220NX M5	M5	0,8	70	8	6	4,9	371	4,2
2220NX M6	M6	1	80	10	6	4,9	371	5,0
2220NX M8	M8	1,25	90	12,5	8	6,2	371	6,8
2220NX M10	M10	1,5	100	15	10	8	371	8,5
4220NX M12	M12	1,75	110	17,5	9	7	376	10,2

Materiaal	Vc m/min	F = toerental x spoed
Staal	Ongelegeerd staal	22-24m/min
	ST37 ST52/3	
	Laaggelegeerd staal	18-22m/min
	C45 C60	
	Hoog gelegeerd staal	7-12m/min
	36CrNiMo4 42CrMo4	
Roestvrijstaal	RVS ferritisch / martenitisch	10m/min
	403-416 - 420	
	RVS Austenitisch	12m/min
	303-304-316	
Gietijzer	Grijs gietijzer GG10-GG15-GG20	30m/min
	GG25-GG30-GG35-GG40	
	Nodulair gietijzer	22m/min
	GGG40-GGG50-GGG60-GGG70	
Non-Ferro	Aluminium	30-35m/min