




Afmetingen



Artikelnummer	d1	Spoed	l1	l2	d2	a	DIN	 Ø mm
4050MF8X1	M8	1	90	13	6	4,9	374	7,0
4050MF10X1	M10	1	90	12	7	5,5	374	9,0
4050MF10X1,25	M10	1,25	100	15	7	5,5	374	8,8
4050MF12X1	M12	1	100	14	9	7	374	11,0
4050MF12X1,25	M12	1,25	100	14	9	7	374	10,8
4050MF12X1,5	M12	1,5	100	14	9	7	374	10,5
4050MF14X1,5	M14	1,5	100	16	11	9	374	12,5
4050MF16X1	M16	1	100	16	12	9	374	15,0
4050MF16X1,5	M16	1,5	100	16	12	9	374	14,5
4050MF18X1,5	M18	1,5	110	20	14	11	374	16,5
4050MF20X1,5	M20	1,5	125	20	16	12	374	18,5
4050MF22X1,5	M22	1,5	125	20	18	14,5	374	20,5
4050MF24X1,5	M24	1,5	140	22	18	14,5	374	22,5

Materiaal		Vc m/min	F = toerental x spoed
Staal	Ongelegeerd staal	4-6m/min	
	ST37 ST52/3		
	Laaggelegeerd staal	4-6m/min	
	C45 C60		
Gietijzer	Nodulair gietijzer	4-7m/min	
	GGG40-GGG50-GGG60-GGG70		
	Koper	12-18m/min	
Non-Ferro	Aluminium	12-18m/min	