




Afmetingen



Artikelnummer	d1	Spoed	l1	l2	d2	a	DIN	 Ø mm
T648M3	M3	0,5	56	9	3,5	2,7	371	2,5
T648M4	M4	0,7	63	12	4,5	3,4	371	3,3
T648M5	M5	0,8	70	13	6	4,9	371	4,2
T648M6	M6	1	80	15	6	4,9	371	5,0
T648M8	M8	1,25	90	18	8	6,2	371	6,8
T648M10	M10	1,5	100	20	10	8	371	8,5
T649M12	M12	1,75	110	23	9	7	376	10,2
T649M14	M14	2	110	25	11	9	376	12,0
T649M16	M16	2	110	25	12	9	376	14,0
T649M18	M18	2,5	125	30	14	11	376	15,5
T649M20	M20	2,5	140	30	16	12	376	17,5

Materiaal		Vc m/min	F = toerental x spoed
Staal	Ongelegeerd staal	10-12m/min	
	ST37 ST52/3		
	Laaggelegeerd staal	8-10m/min	
	C45 C60		
	Hoog gelegeerd staal	6-8m/min	
36CrNiMo4 42CrMo4			
Gietijzer			
	Nodulair gietijzer	8-10m/min	
	GGG40-GGG50-GGG60-GGG70		
Non-Ferro	Koper	12-18m/min	
	Aluminium		
		12-18m/min	